


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A01D 34/73		A1	(11) International Publication Number: WO 97/19584
			(43) International Publication Date: 5 June 1997 (05.06.97)
(21) International Application Number: PCT/SE96/01580 (22) International Filing Date: 29 November 1996 (29.11.96) (30) Priority Data: 95/14457 30 November 1995 (30.11.95) FR 9601287-7 3 April 1996 (03.04.96) SE (71) Applicant (for all designated States except US): HUSQVARNA AKTIEBOLAG [SE/SE]; S-561 82 Huskvarna (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): LEGRAND, Emmanuel [FR/FR]; Le Bourg, F-01480 Villeneuve (FR). LANDEN, Göran [SE/SE]; Videgatan 12, S-561 38 Huskvarna (SE). (74) Agent: ERIXON, Bo; Aktiebolaget Electrolux (publ), Group Patents & Trademarks, S-105 45 Stockholm (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: CUTTING FILAMENT**(57) Abstract**

The present invention relates to a cutting filament intended for trimming and cutting vegetation, such a cutting filament being used on rotary-head motorized cultivators such as brush cutters and edge trimmers. During use such cutting filaments generate a substantial and unpleasant amount of high-frequent noise which is added to the noise of the motor for driving the rotary head. These noises lead to outdoor noise pollution. Legislative requirements aiming to limit the noise to a level deemed to be acceptable are being drawn up and could shortly come into force. The cutting filament according to the present invention is characterized in that the cutting filament (1; 10') has undulations (2; 6; 12') that recur in the longitudinal direction of the cutting filament (1; 10').